

REPLACEMENT COMPONENTS (CONSUMABLES)

Component	Part No.	Recommended Replacement Frequency
Firewall X UV Lamp - 13W Watt	CT-2090-IBO-00	Every 6 months
Carbon Block Cartridge (CBC) Filter * Assembly w/Lead and Cyst Reduction	FT-0063-WLT	Every 6 months, or as required 1 Micron Inline Assembly w/BioCote Housing
1 Micron CBC Filter Cartridge with Lead and Cyst Reduction *	K-FT-0064-WLT	Replacement Cartridge for FT-0063-IL- WLT
Sediment Filter Assembly	FT-0053-IL-WLT	Every 6 months, or as required Inline Assembly with BioCote Housing
Sediment Filter Cartridge	K-FT-0055-WLT	Replacement Cartridge for FT-0053-IL- WLT
Hot Tank	HT-0013-L00-00	Replace every 3-5 years depending on usage

^{*}Required for NSF-55 and NSF P231 Certification.

<u>CAUTION!</u> Use only Waterlogic Replacement parts that can be obtained from *Waterlogic* or an Authorized Waterlogic Dealer, failure to do so will void the Warranty.

See Installation and Service Manual for additional information.

Hot Tank Service

Hot Tanks (with controls) must be replaced at least every 3-5 years depending on usage. Descaling hot tank may be required on a regular basis depending upon filtration and local water conditions. See Installation and Service Manual for further details.

Surface Cleaning

Clean on a regular basis with damp lint free cloth. Never use harsh chemicals (alcohol or acid based) or abrasive agents on any part of the product to avoid damage. A mild cleaner such as Simple Green or equivalent is recommended.

DISPOSAL

End of Life

At the **end of this product's life**, ensure that it is disposed of in an environmentally friendly manner which is fully compliant **with all Federal/State/Local Requirements and Guidelines**. Do not dispose of this appliance with normal household or business waste.

WL7 FW Manual Page 17 - Revision: 10-30-2020