

## MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL – PART NUMBER
<i>WL2FLT Firewall</i>	<i>Waterlogic WL2FLT</i> - Cold and Hot (China)	WL2FLT-FX-HC
	F-2FXFL-FT-HC-TSL111NX-BS-WLU Serial Number Prefix: <b>LE4H247BS</b>	
	<i>Waterlogic WL2FLT</i> - Cold and Hot (USA)	WL2FLT-FZ-HC
	F-2FZFL-FT-HC-TSL111NX-BS-LIN Serial Number Prefix: <b>LE?H???BS</b>	

## SPECIFICATIONS

ITEM	<i>WL2FLT Tower</i>
Water Connection	¼" Quick Connect
Cold Water Temperature	Cold Water Temperature – Factory Set Point 5°C (41°F) Adjustable to 5°- 8°C (41° - 46.4° F)
Cold Tank Size	Tower – 4 Liters (1 Gallon)
Hot Water Temperature	85-87°C (185-189°F) Thermistor Control Hot Tank
Hot Tank Size	1.5 Liters (.40 Gallons)
Hot Water Manual Reset Overload	105°C (221°F)
Recommended Incoming Feed Pressure & Flow	Pressure 40-60 psi (275-414 kPa) – Use Pressure Regulator Input Flowrate 2 – 4 Liters per Minute (0.5 – 1.0 gpm)
Maximum Service Pressure	100 psi (689 kPa) – Use Pressure Regulator when pressure is over 60 psi
Rated Service Flow Out	1.6 Liters per Minute (0.42 Gallons per Minute) – Firewall™ Purification
Environmental Temperature	2°- 37°C (35°- 100°F) Do not use Outdoors
UV Lamp	15 Watts
Heater	500 W
Refrigerant Gas	R134a, 38g, 1.34 ounces
R134a Pressures	High (280 psi), Low (90 psi)

### SHIPPING SPECIFICATIONS

<b>ITEM</b>	<b><i>WL2FLT</i></b>
Width/Depth/Height	349mm x 363mm x 1176mm 13.74" x 14.29 x 46.30"
Weight (dry) Unit Only	33.0 kg (72.8 pounds)

### ELECTRICAL SPECIFICATIONS

<b>ELECTRICAL SUPPLY</b>	<b>120V/60Hz</b>	<b>15 Amp Service</b>
<b>COMPONENT</b>	<b>POWER (approximate)</b>	<b>AMP DRAW (approximate)</b>
Heater	500	4.2 Amps
Compressor	168	1.4 Amps
UV Lamp System	36	0.3Amps
<b><i>WL2FLT</i> TOTAL</b>	<b>706</b>	<b>5.9 Amps</b>

