

MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL – PART NUMBER
WL350 Counter Top	Waterlogic WL350 Counter Top - Cold and Hot	12-CHCMFW3
	F-2FW-M-HC-TT-CS-INN Serial Number Prefix: 49 or LF2H216CS	
WL350 Tower	Waterlogic WL350 Tower - Cold and Hot	12-CHCFW3
	F-2FW-FS-HC-TT-CS-INN Serial Number Prefix: 46 or LF1H216CS	

SPECIFICATIONS

ITEM	WL350 Counter Top	WL350 Tower
Water Connection	¼" Quick Connect	
Cold Water Temperature	Cold Water Temperature – Factory Set Point 5°C (41°F) Adjustable to 1.1°- 12.2°C (34° - 54° F)	
Cold Tank Size	Countertop - 2 Liters (.5 Gallons) Tower – 4 Liters (1 Gallon)	
Hot Water Temperature	87°C (187°F)	
Hot Tank Size	1.6 Liters (.42 Gallons)	
Hot Water Manual Reset Overload	105°C (221°F)	
Recommended Incoming Feed Pressure	40-60 psi (275-414 kPa) – Use Pressure Regulator	
Maximum Service Pressure	100 psi (689 kPa) – Use Pressure Regulator	
Rated Service Flow Out	1.89 Liters per Minute (0.5 Gallons per Minute) – Firewall Purification	
Environmental Temperature	2°- 37°C (35°- 100°F)	
UV Lamp	15 Watts	15 Watts
Heater	500 W	
Refrigerant Gas Compressor: CO-0020-L000	R134a, 43g, 1.52 ounces	R134a, 53g, 1.87 ounces
Refrigerant Gas Compressor: 10-2200(CO-9001A)	R134a, 40g, 1.41 ounces	R134a, 65g, 2.29 ounces
R134a Pressures	High (230 psi), Low (90 psi)	

SHIPPING SPECIFICATIONS

ITEM	<u>WL350 Counter Top</u>	<u>WL350 Tower</u>
Width/Depth/Height	34cm x 37cm x 45cm 13.5" x 14.5" x 17.75" #	34cm x 41cm x 104cm 13.5" x 14.5" x 41"
Weight (dry)	26.3 kg (58 pounds)	30 kg (66 pounds)

#WL350 Counter Top is 17.75 in. tall and may not fit between countertops and cabinets - Check installation to ensure adequate clearance.

ELECTRICAL SPECIFICATIONS

ELECTRICAL SUPPLY	120V/60Hz	15 Amp Service
COMPONENT	POWER (approximate)	AMP DRAW (approximate)
Heater	504	4.2 Amps
Compressor	216	1.8 Amps
UV Lamp System	18	0.15 Amps
WL350 TOTAL	738	6.15 Amps

#WL350 Counter Top is 17.75 in. tall and may not fit between countertops and cabinets - Check installation to ensure adequate clearance.