

## WL380 MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL - PART NUMBER
<i>WL380</i>	<i>WL380</i> Cold, Ambient, Hot, Extra Hot F-3FW-FS-HCA-TT-BL-WLU / Serial # Prefix <b>83</b>	WL380

## SPECIFICATIONS

<u>ITEM</u>	
Water Connection	¼" Quick Connect
Cold Water Temperature	41° F (5°C) Factory Set Point Adjustable Thermostat Range: 35°F (2°C) to 46°F (8°C)
Cold Tank Size	4.0 Liter
Hot Water Temperature	87°C (189°F) Factory Set Point
Extra Hot Water Output	95°C (203°F) Factory Set Point
Hot Tank Size	1.6 Liter Stainless Tank
Hot Water Manual Reset Overload	105°C (221°F)
Recommended Incoming Feed Pressure	40-60 psi (275-414 kPa) – Use Pressure Regulator
Maximum Service Pressure	100 psi (689 kPa) – Use Pressure Regulator
Rated Service Flow Out	1.89 Liters per Minute (0.5 Gallons per Minute) – Firewall Purification
Environmental Temperature	2°- 37°C (35°- 100°F)
UV Lamp	13 Watts
Heater	500 Watts
Refrigerant Gas	R134a, 2.12 ounces (0.06 kg)
R134a Pressures	High (230 psi), Low (90 psi)

\*See Filter Performance Data Sheet for NSF/ANSI 53 Specifications

### WL380 ELECTRICAL SPECIFICATIONS

<b>ELECTRICAL SUPPLY</b>	<b>AC 120V/60Hz, 1 PHASE</b>	<b>15 Amp Service Required</b>
<b>COMPONENT</b>	<b>POWER (approximate)</b>	<b>DRAW (approximate)</b>
Heater	500 Watts	4.17 Amps
Compressor	156 Watts	1.3 Amps
Controls	18 Watts	0.15 Amps
Firewall UV System	13 Watts	0.11 Amps
<b>WL380 TOTAL</b>	<b>687 WATTS</b>	<b>5.7 AMPS</b>

### WL380 SHIPPING SPECIFICATIONS

<b>ITEM</b>	<b>Box Size</b>	<b>Dry Weight</b>
Width/Depth/Height	470 mm x 445 mm x 1245 mm 18.5" x 17.5" x 49"	29.5 kg 65 pounds