

MODEL/PART DESIGNATIONS

| BRAND NAME | DESCRIPTION | MODEL – PART NUMBER |
|--------------|---------------------------------|---------------------|
| <i>WL800</i> | Waterlogic WL800 – Cold and Hot | 16-MAXH2 |

SPECIFICATIONS

| <u>ITEM</u> | <u>WL800</u> |
|------------------------------|---|
| Water Connection | ¼" Quick Connect |
| Cold Water Temperature | Cold Water Temperature – Factory Set Point 5°C (41°F) |
| Hot Water Temperature | 70 - 95°C (158-203°F) Programmable |
| Recommended Service Pressure | 40-60 psi (275-414 kPa) – Use Pressure Regulator |
| Maximum Working Pressure | 60 psi (414 kPa) – Use Pressure Regulator |
| Environmental Temperature | 2 - 37°C (35-100°F) |
| Refrigerant Gas | R134a – 2.05 oz. (65 grams) - Hi (290 psi) Low (90 psi) |
| R134a Pressures | High (290 psi), Low (90 psi) |
| RO Output | 284 Liters per day (75 Gallons per Day) |

SHIPPING SPECIFICATIONS

| <u>ITEM</u> | <u>DIMENSIONS</u> |
|---|--|
| Width/Depth/Height | 445 mm (17.5 inches) x 508mm (20 inches) x 1257mm (49.5) |
| Weight – Dry (w/o packaging) | 42 kg (93 lb.) |
| Shipping Information (length x width x height) | 546.1 mm (21.5 inches) x 635 mm (25 inches) x 1321 (52 inches) 4 units per pallet |
| Shipping Weight – Dry | 46 kg (103 lb.) |

ELECTRICAL SPECIFICATIONS

| |
|-----------------------------------|
| 15 Amp Service* |
| AMP DRAW (approximate) = 6.5 Amps |